

Article Information

Submitted: November 24, 2023

Approved: December 13, 2023

Published: December 14, 2023

How to cite this article: Harichane A, Belalia F. Influence of Polycarboxylate Superplasticizer on the Calorimetric and Physicomechanical Properties of Mortar. *IgMin Res.* Dec 14, 2023; 1(2): 133-135. IgMin ID: igmin128; DOI: 10.61927/igmin128; Available at: www.igminresearch.com/articles/pdf/igmin128.pdf

Copyright license: © 2023 Harichane A, et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Keywords: Cement; Calorimeter; Hydration; Resistance; Polycarboxylate superplasticizer

Research Article

Influence of Polycarboxylate Superplasticizer on the Calorimetric and Physicomechanical Properties of Mortar

Alya Harichane* and Fatiha Belalia

Institute of Science, University Center of Tipaza, 42000, Algeria

***Correspondence:** Alya Harichane, Institute of Science, University Center of Tipaza, 42000, Algeria, Email: harichane.alya@cu-tipaza.dz



Abstract

The use of polycarboxylate ether superplasticizer PCE in the preparation of mortars and concretes influences the hydration kinetics and the amount of total heat released. This leads to a modification of certain properties of the mortar, namely workability, calorimetry and mechanical resistance. In this study two ether polycarboxylate superplasticizers with different chemical structures were used; they were incorporated at different dosages into a standardized cement-based mortar. The objective of this work is to study the effectiveness of these superplasticizers and to select the most compatible product with cement and the most suitable for use according to the climates of the country. The impact of superplasticizers on fresh cement was studied by measuring the Marsh cone flow time and calorimetric measurement. In the hardened state, the mechanical properties were provided by measuring the compressive strength. The results show that low dosages of ether polycarboxylate superplasticizer promote grain hydration and produce more heat. On the other hand, high dosages delay the contact of the cement grains with the mixing water and cause a reduction in the final heat released and a delay in setting. The ether polycarboxylate superplasticizer with high carboxylic density gives the best mechanical resistance compressive at 7 and 28 days.

Introduction

Among the most important superplasticizers currently used in the preparation of concrete, we find polycarboxylates [1], preferred for their ability to improve the properties of concrete [2,3] and to give it better mechanical behavior due to the reduction in the necessary W/C ratio. The type of polycarboxylate used and its molecular structure influence the rheological behavior of the pastes [4-6]. These polymers influence the heat of hydration as well as the quantity of hydration products formed. Their dispersion effect is linked to adsorption which depends on the compatibility between superplasticizer and cement. The dispersion of grains promotes direct contact with the mixing water, which increases the quantity of hydrates formed and improves the mechanical properties of mortars or concretes.

The aim of our study is to compensate for the lack of information by analyzing the effect of two polycarboxylates of different chemical structures on the physico-mechanical and calorific properties of cement pastes.

Materials and methods

Materials

Superplasticizer: Two types of superplasticizers produced in Algeria were used: Medaflow 30 - designated as PCE₁ and Polyflow SR 5400 - designated as PCE₂. The two polymers are new-generation, non-chlorinated, and are based on modified polycarboxylic ether. The characteristics of the superplasticizers, according to their technical data sheet, are presented in Table 1.

Table 1: Properties of the PCEs.

Property	Type of superplasticizer	
	PCE ₁	PCE ₂
Dry extract	30% ± 1%	30% ± 1%
pH	3.35	4.46
Density (g/cm ³)	1.07 ± 1	1.07 ± 0.02
Mn (Da)	4 771	13 621
Mw (Da)	5 157	15 959
PDI	1.081	1.172
Carboxyl content (mmol/g)	1.95	1.87

PDI: Polydispersity Index; Mn: Number average molecular weight of PCE; Mw: Weight average molecular weight of PCE

Portland cement: The cement used in this work is a composite portland cement (CEM II/ A-L 42.5 N) containing 17% clay, 80% limestone, 2% sand and 1% iron ore, produced by the company Mitidja Cements; Algeria. The chemical, mineralogical, and physical characteristics are shown in Table 2.

Experimental measurements

Compressive strength: The compressive strength was measured according to the EN 196-1 protocol. A batch of three mortar specimens was prepared with cement, water, standard sand (c:w:s = 1: 0.5: 3), and super-plasticizers (P/C = 0; 0.2; 0.4; 0.6; 0.8; 1%). After casting for 1 day, samples were demolded and cured in water for 1, 7 and 28 days. The compressive strengths of the samples were determined.

Hydration heat: A semi-adiabatic calorimeter was chosen to measure the heat of hydration of mortar samples prepared with one part cement, three parts sand, and half part water. The mixtures are adjuvanted with different dosages and types of superplasticizers. The mixtures are made with different superplasticizer contents, 0.0.5, 1, 1.5, 2%.

Results and discussions

Compressive strength

Figure 1 shows that SP1 gives the best mechanical compressive strength at 7 and 28 days; he is the most efficient. SP1 is a polycarboxylic ether-type superplasticizer; it is the most efficient. This copolymer has a comb structure; its main chain carries a negatively charged carboxylic group which facilitates the adsorption of the molecule on the surface of the cement particles by electrostatic interaction; The side chains contain polyethylene glycol (PEG) structures that promote dispersion of cement particles due to the steric hindrance they produce [1,2,4]. SP1 is

Table 2: Chemical and Mineralogical composition of the cement.

Chemical characteristics									
designation	PAF	SiO ₂	Al ₂ O ₃	Fe ₂ O ₃	CaO	MgO	SO ₃	K ₂ O	Na ₂ O
%	7.57	19.43	4.69	3.24	63.79	1.40	2.25	0.69	0.22
Mineralogical characteristics									
designation	C3S	C2S	C3A	C4AF					
%	75.83	1.49	6.95	9.86					




Figure 1: Effect of superplasticizer type on mechanical strength.

more efficient compared to SP2; due to its higher carboxylic charge density; the latter improves the dispersion of cement grains and promotes direct contact with the mixing water, which increases the quantity of hydrates formed and improves the mechanical properties of mortars or concretes.

Hydration heat

Figures 2,3 illustrate the evolution of the total exothermic heat provided by different dosages of each superplasticizer. By adding superplasticizer to the mortar, the final heat decreases with increasing superplasticizer dosage; due to the dispersion of grains and the availability of water released by their deflocculation. The superplasticizers delay the contact of the cement grains with the mixing water and cause a reduction in the final heat. Polycarboxylate molecules prefer to attach to C₃A and C₄AF and their hydration products and delay the hydration of C₃S and the formation of CSH and CH [7]; after the addition of 0.5% of a polycarboxylate, the formation of portlandite began after 18 hours of hydration, on the other hand for an ordinary cement without superplasticizer it began after 4 hours. Polycarboxylates delay initial hydration for a long time, since the thickness of the superplasticizer absorption layer interferes with ion diffusion, on the other hand when Ca⁺² ions saturate the surface, the growth of CH eliminates the layer doubles and diffuses the silicates to the surface of the solution [7].

SP1 is the most efficient; it reduces the heat of hydration to 218 J/g after 3 days due to its chemical structure. The carboxylic




Figure 2: Influence of the SP1 dosage on the heat of hydration of a cement mortar.




Figure 3: Influence of the SP2 dosage on the heat of hydration of a cement mortar.

density and molecular weight of the superplasticizer have great effects on the dispersion performance. As the carboxylic density increases, the dispersion capacity of the SP improves [8-10]. PCE1 has the highest carboxylic density in the backbone and moderate molecular weight and has higher adsorption behavior on cement particles; therefore, the lowest heat of hydration. It is therefore compatible with cement.

Conclusion

Superplasticizers are used to improve the mechanical and calorimetric properties of cementitious systems. These anionic polymers adsorb on the surface of the cement grains and cause dispersion of the particles. Fluidity is thus obtained by the deflocculation of the cement grains and the release of the water retained in the flocculates. A consecutive reduction in the heat of hydration as a function of the superplasticizer dosage is then mentioned.

References

1. Harichane A, Benmounah A. Influence of Polycarboxylic Ether-based Superplasticizers (PCE) on the Rheological Properties of Cement Pastes. *J Mater Eng Struct.* 2021; 8: 325–339.
2. Lei L, Hirata T, Plank J. 40 years of PCE superplasticizers-History, current state-of-the-art, and an outlook. *Cem Concr Res.* 2022; 157: 106826.
3. Harichane A, Seghir NT, Niewiadomski P, Sadowski Ł. Effectiveness of the Use of Polymers in High-Performance Concrete containing Silica Fume. *Polymers.* 2023; 15(18): 3730. <https://doi.org/10.3390/polym15183730>
4. Harichane A, Benmounah A, Plank J. Effect of Molecular Weight and Carboxylic Density of Polycarboxylates Ether Superplasticizer on Its Performance in Cement Pastes. *J Mater Eng Struct.* 2023; 10: 283-292.
5. Sha S, Wang M, Shi C, Xiao Y. Influence of the structures of Polycarboxylate superplasticizer on its performance in cement-based materials-a review. *Constr Build Mater.* 2020; 233: 117257.
6. Kai K, Heng Y, Yingbin W. Effect of chemical structure on dispersity of polycarboxylate superplasticizer in cement paste. *Adv Cem Res.* 2019; 32: 456–464.
7. Chen S, Sun S, Chen X, Zhong K. Effects of core-shell polycarboxylate superplasticizer on the fluidity and hydration behavior of cement paste. *Colloids and Surfaces A: Physicochemical and Engineering Aspects.* 2020; 590: 124464. doi:10.1016/j.colsurfa.2020.124464.
8. Kong F, Pan L, Wang C, Zhang D, Xu N. Effects of polycarboxylate superplasticizers with different molecular structure on the hydration behavior of cement paste. *Construction and Building Materials.* 2016; 105:545-553. doi:10.1016/j.conbuildmat.2015.12.178.
9. Papo A, Piani L. Effect of various superplasticizers on the rheological properties of Portland cement pastes. *Cement and Concrete Research.* 2004; 34(11): 2097-2101. doi:10.1016/j.cemconres.2004.03.017.
10. Alonso MM, Palacios M, Puertas F. Compatibility between polycarboxylate-based admixtures and blended cement pastes. *Cement and Concrete Composites.* 2013; 35(1): 151-162. doi:10.1016/j.cemconcomp.2012.08.020.

How to cite this article: Harichane A, Belalia F. Influence of Polycarboxylate Superplasticizer on the Calorimetric and Physicomechanical Properties of Mortar. *IgMin Res.* Dec 14, 2023; 1(2): 133-135. IgMin ID: igmin128; DOI: 10.61927/igmin128; Available at: www.igminresearch.com/articles/pdf/igmin128.pdf

INSTRUCTIONS FOR AUTHORS

IgMin Research | STEM, a Multidisciplinary Open Access Journal, welcomes original contributions from researchers in **S**cience, **T**echnology, **E**ngineering, and **M**edicine (STEM). Submission guidelines are available at www.igminresearch.com, emphasizing adherence to ethical standards and comprehensive author guidelines. Manuscripts should be submitted online to submission@igminresearch.us.

For book and educational material reviews, send them to STEM, IgMin Research, at support@igminresearch.us. The Copyright Clearance Centre's Rights link program manages article permission requests via the journal's website (<https://www.igminresearch.com>). Inquiries about Rights link can be directed to info@igminresearch.us or by calling +1 (860) 967-3839.

<https://www.igminresearch.com/pages/publish-now/author-guidelines>

APC

In addressing Article Processing Charges (APCs), IgMin Research: STEM recognizes their significance in facilitating open access and global collaboration. The APC structure is designed for affordability and transparency, reflecting the commitment to breaking financial barriers and making scientific research accessible to all.

IgMin Research - STEM | A Multidisciplinary Open Access Journal fosters cross-disciplinary communication and collaboration, aiming to address global challenges. Authors gain increased exposure and readership, connecting with researchers from various disciplines. The commitment to open access ensures global availability of published research. Join IgMin Research - STEM at the forefront of scientific progress.

<https://www.igminresearch.com/pages/publish-now/apc>

WHY WITH US

IgMin Research | STEM employs a rigorous peer-review process, ensuring the publication of high-quality research spanning STEM disciplines. The journal offers a global platform for researchers to share groundbreaking findings, promoting scientific advancement.

JOURNAL INFORMATION

Journal Full Title: **IgMin Research-STEM** | A Multidisciplinary Open Access Journal

Journal NLM Abbreviation: IgMin Res

Journal Website Link: <https://www.igminresearch.com>

Category: Multidisciplinary

Subject Areas: **S**cience, **T**echnology, **E**ngineering, and **M**edicine

Topics Summation: 173

Organized by: IgMin Publications Inc.

Regularity: Monthly

Review Type: Double Blind

Publication Time: 14 Days

Google Scholar: <https://www.igminresearch.com/gs>

Plagiarism software: iThenticate

Language: English

Collecting capability: Worldwide

License: Open Access by **IgMin Research** is licensed under a Creative Commons Attribution 4.0 International License. Based on a work at **IgMin Publications Inc.**

Online Manuscript Submission:

<https://www.igminresearch.com/submission> or can be mailed to submission@igminresearch.us